GRENDENE CHAIRS

TECHNICAL SHEET MOD. 1155 PADDED VERSION			55
			58-83 60
DESCRIPTION	:	Stool with padded and upholstered se	eat and backrest, with glides
BASE	:	5-spoke chromed base, semi-oval pip	pe 40x20x1,5
GLIDES	:	Polypropylene with steel insert	
GAS SPRING	:	Chromed steel pipe Ø 50x1,5 Gas high adjustment stroke 265 mm	
FOOTREST	:	Die-cast aluminum, adjustable Ø 460	mm
PLATE	:	Plate in pressed sheet metal 30/10 thi powder	ick, painted with epoxy
INTERNAL SEAT AND BACKREST	:	Multilayers of beech and poplar wood	d 10 mm thick
BACKREST FRAME	:	Chromed steel rod Ø 10 mm, in heigh	nt and depth adjustable
PADDINGS		Polyurethane resin Backrest 30 mm thick Density 30 Seat 40 mm thick Density 30	

UPHOLSTERY	•••	According to upholstery chart
PACKAGING	•	N° 01 piece per carton
WEIGHT	:	Kg 10
CUBAGE	:	Cbm 0,10

GRENDENE CHAIRS

TECHNICAL SHEET MOD. 1155 POLYURETHANE		
DESCRIPTION	:	Stool with seat and backrest in polyurethane, with glides
BASE	:	5-spoke chromed base, semi-oval pipe 40x20x1,5
GLIDES	:	Polypropylene with steel insert
GAS PSRING	:	Chromed steel pipe Ø 50x1,5 Gas high adjustment stroke 265 mm
FOOTREST	:	Die-cast aluminum, adjustable
PLATE	:	Plate in pressed sheet metal 30/10 thick, painted with epoxy powder
INTERNAL SEAT AND BACKREST	:	Multilayers of beech and poplar wood 10 mm thick
PADDINGS	:	Cold foam integral polyurethane
BACKREST FRAME	:	Chromed steel rod Ø 10 mm, in height and depth adjustable

PACKAGING	:	N° 01 piece per carton
WEIGHT	:	Kg 10
CUBAGE	•	Cbm 0,10

All measurements must be considered indicative.

Measures vary according to the finish of the product and the presence of castors or glides.